

RESERVE COPY

PATENT SPECIFICATION

695,288



Date of filing Complete Specification July 2, 1951.

Application Date July 10, 1950.

No. 17260/50.

Complete Specification Published Aug. 5, 1953.

Index at acceptance:—Class 38(iv), A2b6.

COMPLETE SPECIFICATION

Apparatus for Generating Electricity

We, JAMES ARTHUR PETERS, RICHARD CHARLES BIRD and HAROLD GRAHAM PUTTICK, all British Subjects, all of Richborough Works, Sandwich, Kent, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

10 This invention relates to apparatus for generating electricity and particularly to that type of apparatus in which, when there is no call for electricity the generator is at rest, but is started as soon as
15 such call occurs and is again stopped when the demand for electricity ceases.

In apparatus of the above particular type, there is usually provided a source of direct current connected in series with
20 the winding of a main controlling relay and the load circuit. This main controlling relay, when operated as the result of the operation of a switch to connect a consuming device (lamp or other device)
25 to the load circuit brings about the starting of an internal combustion engine to drive a generator, usually an alternator. When the generator is supplying power to the load circuit, the direct current from
30 the source of such is cut out and the main controlling relay is held operated by current derived from that flowing from the generator to the load circuit, so that the main controlling relay now depends, for
35 its continued operation, upon such flow of current in the load circuit, that is, ultimately, upon there being a consuming device connected to the load circuit. As soon as all consuming devices are
40 switched off, and consequently no current from the generator is flowing in the load circuit, the main controlling relay is de-energised and released, thereby bringing about the stopping of the internal combustion engine. Apparatus as described in
45 this paragraph is "apparatus of the type referred to" when that phrase is used herein.

The present invention relates particularly to an improved circuit arrangement,
50 controlled mainly or in part by the main controlling relay, for respectively starting and stopping the internal combustion engine, the improvement being directed,
55 in general, to ensuring that the time that current is applied to the engine starting device is automatically determined, that (and this is particularly important if the internal combustion engine is a diesel engine) the engine stopping device shall
60 be operated for a sufficiently long time to ensure stopping in spite of the fact that the engine is hot and might, if the stopping device were released too soon, start up again, and that if after all consuming devices have been switched off
65 (and stopping conditions have been thereby initiated) it will not be necessary for the stopping cycle to be completed before current is again supplied to the
70 load circuit.

According to a principal feature of this invention, apparatus of the type referred to includes a first normally-closed contact of the main controlling relay in series with
75 a condenser and with the source of direct current, and a normally-open contact of the main controlling relay in series with an engine starting relay connected across said first condenser.
80

According to another principal feature of the invention apparatus of the type referred to includes a first normally-open contact of a contactor device (whose winding is connected across the generator) in
85 series with a condenser, and a second normally-closed contact of the main controlling relay in series with an engine stopping relay connected across said second condenser.
90

In apparatus embodying both said principal features of the invention, a pair of normally open contacts of said engine stopping relay, or preferably, of said contactor device may be connected across said
95 first condenser thereby to prevent charging of said first condenser during the engine stopping cycle.

Price 4s 6d

In apparatus embodying either or both of the said principal features, in which the generator is an alternator, there may be connected in series with the load circuit at a position in which current flows from said generator only when a consuming device is switched in, a saturated choke across which is connected the winding of the main controlling relay in series with a rectifier.

A circuit according to the invention is illustrated in the accompanying drawing. In the circuit illustrated, a source of direct current (not shown) has one of its terminals, as shown the positive terminal, connected to a first terminal L1 of the load circuit (not shown) through a normally-closed contact t2 of a contactor device and its other terminal (-) connected to the other terminal L2 of the load circuit through the winding of a main controlling relay A and a rectifier R. An alternating current generator G has one terminal g1 connected through normally-open power contacts tp1 of said contactor device, to said one terminal L1 of the load circuit and its other terminal g2 connected, through other normally-open power contacts tp2 of said contactor device and a saturated choke Ch in series with each other, to the said other terminal L2 of the load circuit. The core of choke Ch should be of one of the ferro-magnetic alloys which are saturable by a very small current. The said other terminal g2 of the alternating current generator is connected to the said other terminal (-) of the source of direct current. A contactor-operating solenoid T is connected across the terminals of the alternator.

There is also connected from said one terminal of the source of direct current to the other terminal of said source a circuit comprising a first resistor R1 in series with a normally-closed contact a1 of the main controlling relay A in series with three circuit elements, namely (1) a normally-open contact e2 of an engine stopping relay or, preferably t3 of the contactor device, (2) a first condenser C1, and (3) a normally-open contact a2 of the main controlling relay A in series with the winding of an engine starting relay D, these last three circuit elements being connected in parallel with each other.

There is further connected from said one terminal of the source of direct current to the other terminal of said source a circuit comprising a second resistor R2 in series with a normally-open contact t1 of the contactor in series with two circuit elements, namely (1) a second condenser C2, and (2) a normally-closed contact a3 of the main controlling relay in series with the winding of an engine stopping

relay E, these last two circuit elements being in parallel with each other.

The engine starting relay D has a normally-open contact d connected in series with an engine starting solenoid, these two elements being connected to opposite terminals of the source of direct current. The engine stopping relay E has a normally-open contact connected in series with a fuel rack shut-off solenoid, or other stopping device, these two elements being likewise connected to opposite terminals of the source of direct current.

The operation of the system according to our invention is as follows: Condenser C1 is held charged by reason of its being connected in series with resistor R1 and normally-closed contacts a1 of the main controlling relay A across the terminals of the source of direct current. When a consuming device switch (not shown) in the load circuit is closed, current flows from the source of direct current, through the contact t2, the switch and consuming device, rectifier R, and the main controlling relay A, and back to the source. The main controlling relay A thereupon operates and at contact a1 opens the charging circuit of condenser C1, and at contact a2 closes a discharging circuit through the winding of the engine starting relay D. The engine starting relay closes its contacts d thereby energising the engine starting solenoid. The capacity of the condenser and the impedance of the engine starting relay together determines the duration of time that the engine starting solenoid shall be energised.

When the engine has been started and the alternator is being driven, current flows from the alternator through the winding T of the contactor device so that the contactor device energises and operates its contacts. Of these contacts tp1 and tp2 connect the alternator G to the load circuit (in series with which it will be recalled, there is connected a saturated choke ch), whilst contacts t2 of the contactor device open the circuit from the source of direct current to the load circuit, and contacts t1 close a charging circuit through resistor R2 to condenser C2. The disconnection of the source of direct current from the load circuit deprives the main control relay A of current from this source; this relay however, receives current due to the drop of potential across the saturated choke ch so that, as long as the alternator is supplying current to the load, the main control relay remains operated, the holding current remaining substantially constant irrespectively of the load current.

When all current-consuming devices have been switched out, and consequently

no current is flowing in the load circuit, the main controlling relay A de-energises, and prepares a discharge circuit for condenser C2 in series with the engine stopping relay E. However, condenser C2 does not discharge through the winding of the engine stopping relay until the speed of the alternator falls so low that the contactor-operating solenoid T receives insufficient current to maintain it operated. Until the contactor de-energises, the second condenser remains connected, by contact t1, across the source of direct current so that it is continually under charging conditions, and the contactor maintains a circuit for the engine stopping relay E so that the engine stopping relay is in fact energised from the source of direct current. When the speed of the alternator G falls so low that the contactor winding is de-energised, condenser C2 is disconnected from the direct current source and is thus able to discharge through the engine stopping relay. The total time of energisation of the engine stopping relay is thus the sum of the time that the contactor-operating solenoid T remains energised and the time that condenser C2 takes to discharge. Thus the engine stopping relay is not directly dependent on the charge in condenser C2 for energisation, since contact t1 of the main contactor device remains closed for a considerable part of the running-down time of the engine and therefore the engine stopping relay is directly operated from the source of direct current, condenser C2 having only a much shorter remaining time to hold the engine stopping relay energised. This arrangement has an important advantage, in that the size of condenser C2 is brought within practicable limits in spite of the considerable time required (especially in the case of diesel engines) for the engine speed to become too low for the engine to restart. It has also another important advantage which, so far as we are aware, cannot be obtained in any other way, viz.: It may be that within a few seconds of all load being switched off, the same or another consuming device is required to be switched on. By any other method than that described above the full cycle of stopping operations would have to take place so that the engine could not start again till the full shut-off period had elapsed. By our method of operation the engine stopping relay E is disconnected by contact a3 of the main controlling relay A immediately a consuming device is switched on again, and the engine starting relay D is prevented from functioning by virtue of condenser C1 having been short circuited by contacts e2 on the

engine stopping relay E or t3 of the contactor device. The engine thus starts again immediately by its own momentum.

It has been indicated above, that it is preferred to connect a contact t3 of the contactor, rather than a contact e2 of relay E, across the elements C1 and a2 in series with D. The function remains the same, i.e. it prevents charging of the first condenser during the engine stopping cycle, because due to the inherent characteristics of its magnetic circuit the contactor does not fall out until the engine has almost come to rest. In that respect the contact t3 behaves in the same way as does contact e2. It provides, however, one important advantage as follows.

The charge on condenser C1 holds starting relay D energised for a period dependent upon the characteristics of the condenser and of the winding of relay D. This period cannot readily be varied in use of the apparatus, and it must therefore be of sufficient duration to ensure that the engine shall start under the worst possible conditions. This is usually about ten seconds. However, if the engine is hot it can be expected to start within one second, and may indeed be capable of starting itself. On many occasions, therefore, the engine may be turned over either unnecessarily or for unnecessarily long periods. This is not good for the engine and unnecessarily drains the battery, particularly with a plant which is required to be continually started and stopped.

It is therefore desirable that some means be provided for varying the starting-time-cycle, making it short when the engine is hot and long when conditions are adverse. In all ordinary circumstances this would call for elaborate thermal relays.

The use of a contact, contact t3, on the contactor device, in place of a contact, contact e2, in relay E provides exactly what is required with no additional complications.

The operation will be understood from the following. The characteristics of the contactor device are such, that although (on a 230 volt plant) it is rated for 230 volts 50 cycles per second it will if the number of cycles be as low as ten per second pull in at a very low voltage, say at 90 volts. Now, in an engine which is run up to speed by the starter motor the c/s rise from zero to 50 more or less in proportion to the rise in voltage, so that due to the low periodicity the contactor will pull in quite early. The time at which this pulling-in occurs is obviously a function of the speed at which the engine is motored up.

If the engine is cold, or if for any reason the speed of the motor remains low, the

contactor would not pull in during motor-
ing, the voltage and c/s of the generator
being too low. Contact t3 would therefore
remain open and the starting relay D
5 would be held operated for the full period
of ten seconds, as determined by the
capacity and characteristics of condenser
c1 and of relay D.

If, on the contrary, the engine were hot
10 the speed would rise quickly to provide an
alternator potential say 90 volts at 15 c/s
the contactor would pull in within a second
or so, condenser c1 would be short cir-
cued and the start time cycle would be
15 cancelled or reduced.

It will therefore be seen that the use
of contact t3 in this circuit provides an
automatic variable time delay to the start
circuit which is directly related to the
20 external conditions affecting the starting
of the engine.

What we claim is:—

1. Apparatus of the type referred to in-
cluding a first normally-closed contact of
25 the main controlling relay in series with
a condenser and with the source of direct
current, and a normally-open contact of
the main controlling relay in series with
an engine starting relay connected across
30 said condenser.

2. Apparatus of the type referred to
including a first normally-open contact of
a contactor device whose winding is con-
nected across the generator, in series with

a condenser, and a second normally-closed 35
contact of the main controlling relay in
series with an engine stopping relay con-
nected across said second condenser.

3. Apparatus according to claims 1 and
2 having a pair of normally-open contacts 40
of said engine stopping relay connected
across the condenser mentioned in claim 1
thereby to prevent charging of said first
condenser during the engine stopping
cycle. 45

4. Apparatus according to claims 1 and
2 having a pair of normally open contacts
of said contactor device connected across
the condenser mentioned in claim 1 there-
by to prevent charging of said condenser 50
during the engine stopping cycle.

5. Apparatus according to any of the
preceding claims in which the generator
is an alternator having connected in series
with the load circuit at a position in which 55
current flows from said generator only
when a consuming device is switched in, a
saturated choke across which is connected
the winding of the main controlling relay
in series with a rectifier. 60

6. Apparatus of the type referred to sub-
stantially as described and illustrated in
the accompanying drawings.

CARPMAELS & RANSFORD,
Agents for Applicants,
24, Southampton Buildings,
Chancery Lane, London, W.C.2.

PROVISIONAL SPECIFICATION

Apparatus for Generating Electricity

We, JAMES ARTHUR PETERS, RICHARD
65 CHARLES BIRD and HAROLD GRAHAM
PUTTICK, all British Subjects, all of
Richborough Works, Sandwich, Kent, do
hereby declare this invention to be de-
scribed in the following statement:—

70 This invention relates to apparatus for
generating electricity and particularly to
that type of apparatus in which, when
there is no call for electricity the genera-
tor is at rest, but is started as soon as such
75 call occurs and is again stopped when the
demand for electricity ceases.

In apparatus of the above particular
type, there is usually provided a source of
direct current connected in series with the
80 winding of a main controlling relay and
the load circuit. This main controlling
relay, when operated as the result of the
operation of a switch to connect a consum-
ing device (lamp or other device) to the
85 load circuit brings about the starting of
an internal combustion engine to drive a
generator, usually an alternator. When the
generator is supplying power to the load
circuit, the direct current from the source
90 of such is cut out and the main controlling

relay is held operated by current derived
from that flowing from the generator to
the load circuit, so that the main control-
ling relay now depends, for its continued
operation, upon such flow of current in 95
the load circuit, that is, ultimately upon
there being a consuming device connected
to the load circuit. As soon as all con-
suming devices are switched off, and con-
sequently no current from the generator 100
is flowing in the load circuit, the main
controlling relay is de-energised and
released, thereby bringing about the stop-
ping of the internal combustion engine.

The present invention relates particu-
larly to an improved circuit arrangement,
controlled mainly or in part by the main
controlling relay, for respectively start-
ing and stopping the internal combustion
engine, the improvement being directed, 110
in general, to ensuring that the time that
current is applied to the engine starting
device is automatically determined, that
(and this is particularly important if the
internal combustion engine is a diesel 115
engine) the engine stopping device shall
be operated for a sufficiently long time to

ensure stopping in spite of the fact that the engine is hot and might, if the stopping device were released too soon, start up again, and that if after all consuming devices have been switched off (and stopping conditions have been thereby initiated) it will not be necessary for the stopping cycle to be completed before current is again supplied to the load circuit.

According to a principal feature of this invention, apparatus of the type referred to includes a first normally-closed contact of the main controlling relay in series with a first condenser and with the source of direct current, and a normally-open contact of the main controlling relay in series with an engine starting relay connected across said first condenser.

According to another principal feature of the invention apparatus of the type referred to includes a first normally-open contact of a contactor device (whose winding is connected across the generator) in series with a second condenser, and a second normally-closed contact of the main controlling relay in series with an engine stopping relay connected across said second condenser.

In apparatus embodying both said principal features of the invention, a pair of normally-open contacts of said engine stopping relay may be connected across said first condenser thereby to prevent charging of said first condenser during the engine stopping cycle.

In apparatus embodying either or both of the said principal features, in which the generator is an alternator, there may be connected in series with the load circuit at a position in which current flows only when a consuming device is switched in, a pre-saturated choke across which is connected the winding of the main controlling relay in series with a rectifier.

In a circuit according to the invention, a source of direct current has one of its terminals connected to a first terminal of the load circuit through a normally-closed contact of a contactor device and its other terminal connected to the other terminal of the load circuit through the winding of a main controlling relay and a rectifier. An alternating current generator has one terminal connected through normally-open contacts of said contactor device to said one terminal of the load circuit and its other terminal connected through other normally-open contacts of said contactor device and a pre-saturated choke in series with each other to the said other terminal of the load circuit. The said other terminal of the alternating current generator is connected to the said other terminal of the source of direct current. A contactor-operating solenoid is connected across the

terminals of the alternator.

There is also connected from said one terminal of the source of direct current to the other terminal of said source, a circuit comprising a first resistor in series with a normally-closed contact of the main controlling relay in series with three circuit elements, namely (1) a normally-open contact of an engine stopping relay, (2) a first condenser, and (3) a normally-open contact of the main controlling relay in series with the winding of an engine starting relay, these last three circuit elements being connected in parallel with each other.

There is further connected from said one terminal of the source of direct current to the other terminal of said source, a circuit comprising a second resistor in series with a normally-open contact of the contactor in series with two circuit elements, namely (1) a second condenser, and (2) a normally-closed contact of the main controlling relay in series with the winding of an engine stopping relay, these last two circuit elements being in parallel with each other.

The engine starting relay has a normally open contact connected in series with an engine starting solenoid, these two elements being connected to opposite terminals of the source of direct current. The engine stopping relay has a pair of normally-open contacts connected with a fuel rack shut-off solenoid, or other stopping device, these two elements being likewise connected to opposite terminals of the source of direct current.

The operation of the system according to our invention is as follows: The first mentioned condenser is held charged by reason of its being connected in series with the resistor and normally-closed contact of the main controlling relay across the terminals of the source of direct current. When a consuming-device switch in the load circuit is closed, current flows from the source of direct current, through the rectifier and the main controlling relay through the switch and consuming device, and back to the source. The main controlling relay thereupon operates and opens the charging circuit of the first mentioned condenser, and closes a discharging circuit through the winding of the engine starting relay. The engine starting relay closes its contacts thereby energising the engine starting solenoid. The capacity of the condenser and the impedance of the engine starting relay together determines the duration of time that the engine starting solenoid shall be energised.

When the engine has been started and the alternator is being driven, current

flows from the alternator through the winding of the contactor device so that the contactor device operates and operates its contacts. Certain of these contacts connect the alternator to the load circuit (in series with which it will be recalled, there is connected a pre-saturated choke), whilst other of the contacts of the contactor receiver open the circuit from the source of direct current to the load circuit, and close a charging circuit through the second resistor to the second condenser. The disconnection of the source of direct current from the load circuit deprives the main control relay of current from this source: this relay however, receives current due to the drop of potential across the pre-saturated choke so that, as long as the alternator is supplying current to the load, the main control relay remains operated, the holding circuit remaining substantially constant irrespectively of the load current.

When all current-consuming devices have been switched out, and consequently no current is flowing in the load circuit, the main controlling relay deenergises, and prepares a discharge circuit for the second condenser in series with the engine stopping relay. However, this second condenser does not discharge through the winding of the engine stopping relay until the speed of the alternator falls so low that the contactor receives insufficient current to maintain it operated. Until the contactor deenergises, the second condenser remains connected across the source of direct current so that it is continually under charging conditions, and the contactor maintains a circuit for the engine stopping relay so that the engine stopping relay is in fact energised from the source of direct current. When the speed of the alternator falls so low that the contactor winding is deenergised, the second contactor is disconnected from the direct current source and is thus able to discharge through the engine stopping relay.

The total time of energisation of the engine stopping relay is thus the sum of the time that the contactor solenoid remains energised and the time that the second condenser takes to discharge. Thus the engine stopping relay is not directly dependent on the charge in the second condenser for energisation, since the main contactor device remains closed for a considerable part of the running-down time of the engine and therefore the engine stopping relay is directly operated from the source of direct current, the second condenser having only a much shorter remaining time to hold the engine stopping relay energised. This arrangement has an important advantage, in that the size of the second condenser is brought within practicable limits in spite of the considerable time required (especially in the case of diesel engines) for the engine speed to become too low for the engine to restart. It has also another important advantage which, so far as we are aware, cannot be obtained in any other way, viz.: It may be that within a few seconds of all load being switched off, the same or another consuming device is required to be switched on. By any other method than that described above, the full cycle of stopping operations would have to take place so that the engine could not start up again till the full shut-off period had elapsed. By our method of operation the shut-off relay is disconnected by a contact of the main controlling relay, immediately a consuming device is switched on again, and the engine starting relay is prevented from functioning by virtue of the first condenser having been short circuited by contacts on the engine stopping relay. The engine thus starts again immediately by its own momentum.

CARPMAELS & RANSFORD,
Agents for Applicants,
24, Southampton Buildings,
London, W.C.2.

Leamington Spa: Printed for Her Majesty's Stationery Office, by the Courier Press.—1953.
Published at the Patent Office, 25, Southampton Buildings, London, W.C.2, from which copies may be obtained.

